

Data sheet

6ES7972-0BA12-0XA0

Product type designation Product description



PROFIBUS bus connector, RS485, screw, without PG socket, 90°
 PROFIBUS bus connector, RS485, screw, without PG socket, 90°
 SIMATIC DP, BUS CONNECTOR FOR PROFIBUS UP TO 12
 MBIT/S 90 DEGREE ANGLE OUTGOING CABLE, 15,8 X 64 X 35,6
 MM (WXHxD), TERMINAT. RESIST. WITH ISOLAT. FUNCTION,
 WITHOUT PG SOCKET

Suitability for use	For connecting PROFIBUS nodes to the PROFIBUS bus cable
---------------------	---

Transmission rate

Transfer rate / with PROFIBUS DP	9.6 kbit/s ... 12 Mbit/s
----------------------------------	--------------------------

Interfaces

Number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
Type of electrical connection	
• for PROFIBUS cables	Screw

Mechanical data

Design of terminating resistor	Integrated resistor combination that can be selected with slide switch
Material / of the enclosure	plastic

Design, dimensions and weight

Width	15.8 mm
Height	64 mm
Depth	35.6 mm
Net weight	10 g

Permitted ambient conditions

Ambient temperature	
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C

Protection class IP	IP20
Product properties, functions, components / general	
Product property	
• silicon-free	Yes
Product component	
• PG connection socket	No
• strain relief	Yes
Standards, specifications, approvals	
Certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
last modified:	16.04.2015